



Adhesive grease for the food industry GLS 388/N2

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



KPF2G-10

ELKALUB GLS 388/N2 is an extremely adhesive aluminium complex soap grease based on partly synthetic base oils with a high resistance to water (also salt water). ELKALUB GLS 388/N2 is suitable for temperatures from -10 °C up to +100 °C. The main areas of application are slow-turning drive elements such as joints, shafts, open cogwheels, sliding motions in the food industry. ELKALUB GLS 388/N2 is most suitable for pairings of nonferrous metals and steel.

[Request product Download data sheet](#)

Base oil

other, poly-alpha-olefin, white oil

Thickener

other, aluminum complex, solid lubricant

Operating temperature

-10 °C bis 100 °C

Viscosity

72 mm²/s

NLGI class

2-weich

Suitable for

- open gears
- racks

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

- guides, curves

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com