



## bearing grease GLS 967/N1-2



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH  
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



KP2N-20

ELKALUB GLS 967/N1-2 is a lubricating grease with best water resistance properties. This high adhesive grease offers excellent anti-corrosion abilities. Applications: slide bars, guide systems, chains to be greased through the chain bolt slide bearings, low-speed roller bearings. ELKALUB GLS 967/N1-2 is NSF H1-registered and is therefore suited for environments with food contact.

[Request product](#) [Download data sheet](#)

### **Base oil**

poly-alpha-olefin, white oil, ester oil

### **Thickener**

inorganic

### **Operating temperature**

-15 °C bis 130 °C

### **Viscosity**

380 mm<sup>2</sup>/s

### **NLGI class**

1-sehr-weich,2-weich

### **Suitable for**

- roller bearing
- slide bearing
- guides, curves

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

## Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

## Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)