



bearing grease VP 889



KP3N-20

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB VP 889 is a rolling and plain bearing grease based on a synthetic and an ester oil. Due to its relatively firm consistency and the high base oil viscosity, the grease is also suitable for the lubrication of more heavily loaded bearings at higher temperatures. A special application is the lubrication of chains in sterilizers. The well-adhering grease provides good corrosion protection and is also sufficiently resistant in a hot steam environment.

[Request product Download data sheet](#)

Base oil

poly-alpha-olefin, white oil, ester oil

Thickener

inorganic

Operating temperature

-15 °C bis 130 °C

Viscosity

380 mm²/s

NLGI class

2-weich,3-mittelfest

Suitable for

- slide bearing

Packaging

- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com