



## Chain and adhesive lubricant FLC 8

ELKALUB FLC 8 is a spray, which is based upon our successful special lubricant ELKALUB LA 8. The product does not contain any additives of solid particles. ELKALUB FLC 8 leaves a lubricating film with E.P. and boundary lubrication properties, has a good creeping ability and protects against corrosion. Up to +80 °C, ELKALUB FLC 8 is very adhesive and resistant to centrifugal forces. The lubricating film is very pressure resistant. ELKALUB FLC 8 has shown good results as a special lubricant for highly loaded chains (also in the open air). The product is also used for the lubrication of open gear wheels, cams, cam plates and spindles. Because of

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

the high adhesion of ELKALUB FLC 8, the product is not recommended for long guiderails, which need an easy start. ELKALUB FLC 8 has antinoise qualities.

[Request product Download data sheet](#)

## Base oil

mineral oil, ester oil

## Thickener

polyurea

## Operating temperature

-20 °C bis 120 °C

## Viscosity

120 mm<sup>2</sup>/s

## Suitable for

- slide bearing
- chains
- open gears
- racks
- guides, curves
- fittings & joints

## Packaging

- 400 ml of aerosol

## Industry

- printing industry
- drive technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

# ELKALUB



*Hochleistungs-Schmierstoffe*  
*High Performance Lubricants*

- furniture industry
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)