



Chain and adhesive lubricant LA 8

ELKALUB LA 8 is a highly viscous special lubricant which at the same time possesses an excellent creeping ability. ELKALUB LA 8 is mainly intended for the lubrication of highly loaded chain transmissions. The very adhesive film with EP and boundary lubrication capabilities, which is formed by ELKALUB LA 8 is extremely resistant against centrifugal forces and pressure. ELKALUB LA 8 is recommended or prescribed by leading printing press

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

manufacturers. ELKALUB LA 8 is used straight for all types of chain transmissions or as an additive (5-20 %) for mineral oils for all points of lubrication which need a particularly adhesive type of lubricant. ELKALUB LA 8 has an anti-noise effect. Examples for application: Delivery chains, guide rails, eccentrics, gripper opening curves, open gear wheels, chain guideways.

[Request product Download data sheet](#)

Base oil

mineral oil, ester oil

Thickener

polyurea

Operating temperature

-5 °C bis 80 °C

Viscosity

6000 mm²/s

Suitable for

- gearboxes & gearing
- chains
- gearboxes & gearing

Packaging

- 1 l can
- 20 l jug
- 200 l barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

Industry

- printing industry
- drive technology
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com