



## Chain and sliding spray FLC 1010/1012 P

ELKALUB FLC 1010/1012 P is an oil spray without any solid lubricants based upon our EP lubricating concentrate ELKALUB LA 1. It is resistant to aging, chemically neutral, dirt dissolving, protects against corrosion, does not become resinous and displaces water from surfaces. After spraying on the parts to be lubricated, there remains only a very thin, transparent and adhesive film. The extremely creeping special lubricant guarantees, that the

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)

lubricating film is also forming in very narrow fits where it lubricates reliably. Slightly rusty or coked parts become mobile again and the loosening is supported. Although ELKALUB FLC 1010/1012 P creeps well into fits, the creeping ability on surfaces is minimal. This is of advantage e.g. for grippers and transport chains. ELKALUB FLC 1010/1012 P is available as a pump spray bottle (300 ml)

[Request product Download data sheet](#)

## Base oil

mineral oil, ester oil

## Operating temperature

-20 °C bis 120 °C

## Viscosity

60 mm<sup>2</sup>/s

## Suitable for

- slide bearing
- chains
- guides, curves

## Packaging

- 300 ml pump spray

## Industry

- printing industry
- drive technology
- furniture industry
- wood industry
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**