



# Fluid grease for the food industry GLS 381/N00-000



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)



GPF00-000K-20

[Request product Download data sheet](#)

## Base oil

white oil

## Thickener

aluminum complex, solid lubricant

## Operating temperature

-20 °C bis 120 °C

## Viscosity

220 mm<sup>2</sup>/s

## NLGI class

000-sehr-fluessig,00-fluessig

## Suitable for

- gearboxes & gearing
- chains
- gearboxes & gearing

## Packaging

- 1 kg can
- 18 kg hobbock
- 50 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

# ELKALUB



*Hochleistungs-Schmierstoffe*  
*High Performance Lubricants*

## Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)