

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



Gear grease for power tools VP 729

KP2K-20

[Request product Download data sheet](#)

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Base oil

mineral oil

Thickener

sodium, sodium

Operating temperature

-20 °C bis 120 °C

Viscosity

340 mm²/s

NLGI class

1-sehr-weich,2-weich

Suitable for

- gearboxes & gearing
- roller bearing
- slide bearing
- gearboxes & gearing

Packaging

- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- power tools

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr