



Grease for the food industry GLS 363/N3



KP3K-20

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB GLS 363/N3 is a high-performance grease for primary use in the food industry. Due to its firm consistency, ELKALUB GLS 363/N3 is suitable for thermally loaded bearings in electric motors and pumps as well as for lubrication and sealing tasks for valves and shaft guides.

[Request product Download data sheet](#)

Base oil

white oil, ester oil

Thickener

other, inorganic

Operating temperature

-25 °C bis 120 °C

Viscosity

150 mm²/s

NLGI class

3-mittelfest

Suitable for

- roller bearing

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com