



Grease for the food industry GLS 364



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



KP2K-10

ELKALUB GLS 364 is a high-performance lubricating grease for application in the food industry. The product is mainly used for the lubrication of antifriction bearings under low load and high speed indexes (ndm [gt] 600.000). ELKALUB GLS 364 is very resistant to water and steam as well as to acid solutions (e.g. fruit acids), alkaline media (e.g. cleansing agents) and salt water. ELKALUB GLS 364 protects efficiently against corrosion. The product is well conveyable in central lubricating systems and miscible with conventional soap greases.

[Request product Download data sheet](#)

Base oil

white oil

Thickener

polyurea

Operating temperature

-10 °C bis 120 °C

Viscosity

72 mm²/s

NLGI class

2-weich

Suitable for

- roller bearing
- slide bearing
- guides, curves

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com