



Grease for the food industry GLS 367/N1

KP1K-10

ELKALUB GLS 367/N1 is a partly synthetic lubricating grease for application in the food industry. The product is extremely adhesive and is suitable for slow-turning antifriction bearings, for slip motions and for the lubrication of chains, valves, spindles, sterilizers etc. ELKALUB GLS 367/N1 is resistant to water (up to +100 °C) as well as to acids and alkalis. ELKALUB GLS 367/N1 is suitable for temperatures from -10 °C up to +130 °C (short-time up to 180 °C). A H1-registration for this penetration class would be possible.

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

[Request product Download data sheet](#)

Base oil

other, white oil

Thickener

inorganic

Operating temperature

-10 °C bis 130 °C

Viscosity

165 mm²/s

NLGI class

1-sehr-weich

Suitable for

- roller bearing
- slide bearing
- racks
- linear guides, ball screws
- valves
- fittings & joints

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- wood industry
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com