



Grease for the food industry GLS 382/N2



KP2K-20

The lubricating grease ELKALUB GLS 382/N2 has been designed for application in roller and slide bearings as well as slipways and open lubricating points.

[Request product Download data sheet](#)

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Base oil

other, white oil

Thickener

aluminum complex, solid lubricant

Operating temperature

-20 °C bis 120 °C

Viscosity

220 mm²/s

NLGI class

2-weich

Suitable for

- guides, curves

Packaging

- 250 g tube
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr