



grease for linear guides VP 874



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



KPHC2H-20

ELKALUB VP 874 has been designed as a food grade - and (NSF) H1 approved grease made for use with linear guide systems. The grease can also be employed for the lubrication of roller bearings. In a test under extreme high load (P/C-value = 0,5) at Bosch - Rexroth, ELKALUB VP 874 could exceed the calculated life time of the grease. The short stroke test did reveal paramount results as well. Bosch - Rexroth particularly recommends ELKALUB VP 874.

[Request product Download data sheet](#)

Base oil

other, white oil

Thickener

polyurea

Operating temperature

-20 °C bis 120 °C

Viscosity

150 mm²/s

NLGI class

2-weich

Suitable for

- roller bearing
- slide bearing
- linear guides, ball screws
- pneumatics

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

Packaging

- 250 g tube
- 100 g cartridge
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- drive technology
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com