



Grease for plastic-steel pairings VP 905

KFHC0M-30

[Request product Download data sheet](#)

Base oil

poly-alpha-olefin, ester oil

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Thickener

solid lubricant, lithium (complex)

Operating temperature

-30 °C bis 120 °C

Viscosity

360 mm²/s

NLGI class

0-halbfluessig, 1-sehr-weich

Suitable for

- gearboxes & gearing
- roller bearing
- slide bearing
- linear guides, ball screws
- valves
- gearboxes & gearing

Packaging

- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- automotive
- power tools
- drive technology
- furniture industry

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com