



High-load grease GLS 131/N2

KP2K-20

ELKALUB GLS 131/N2 is a universal grease with high pressure absorption and very good adhesion. The grease can be used in roller and plain bearings as well as in open lubrication points. The speed characteristic in ball bearings is 250,000 mm / min-1.

[Request product Download data sheet](#)

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Base oil

mineral oil

Thickener

lithium (complex)

Operating temperature

-20 °C bis 130 °C

Viscosity

320 mm²/s

NLGI class

2-weich

Suitable for

- roller bearing
- slide bearing
- guides, curves

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- drive technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

- bearing manufacturer
- plant construction
- miscellaneous

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com