



## high-load grease VP 873



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH  
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



KPFHC2N-20

**ELKALUB VP 873** is a grease for heavily loaded roller bearings (especially tapered and spherical roller bearings, cam rollers).

Due to the high load-bearing capacity and the high wear protection, **ELKALUB VP 873** is also used as a lubricant in open gears. The lubrication points benefit from the adhesive formulation, which is also responsible for a high level of corrosion protection and water resistance. The addition of solid lubricants supports sliding pairings and ensures emergency running properties.

**ELKALUB VP 873** is suitable for metal-plastic combinations. Due to the diversity of plastic materials, a previous resistance test is recommended.

A special application of **ELKALUB VP 873** is as an assembly paste for stainless steel screw connections in the food industry. The grease prevents cold welding.

[Request product Download data sheet](#)

### **Base oil**

other, white oil

### **Thickener**

polyurea, solid lubricant

### **Operating temperature**

-20 °C bis 140 °C

### **Viscosity**

460 mm<sup>2</sup>/s

### **NLGI class**

1-sehr-weich,2-weich

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

## Suitable for

- roller bearing
- slide bearing
- open gears
- racks
- guides, curves

## Packaging

- 250 g tube
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

## Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- drive technology
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**