



## High-load silicone grease GLS 795/N2

KPFSi2R-40

ELKALUB GLS 795/N2 is a synthetic high-temperature grease for the lubrication of roller and antifriction bearings of low speed in the temperature range from -40 °C up to +200 °C.

ELKALUB GLS 795/N2 is resistant to water and water vapour. In the hot air stream the application is limited to +120 °C. Attention: It is generic to silicone greases containing PTFE

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

that there may occur explosive decomposition reactions in conveyor systems with high pressures and entrapped air. The suction of air, rapid increase in pressure as well as high pressures have to be avoided by means of suitable construction. Deaerate the whole system before putting into operation! Base oil viscosity at 25 ° C: 5000 mm<sup>2</sup>/s

[Request product Download data sheet](#)

## Base oil

silicone

## Thickener

solid lubricant

## Operating temperature

-40 °C bis 200 °C

## Viscosity

4500 mm<sup>2</sup>/s

## NLGI class

2-weich

## Suitable for

- assembly grease / fittings / o-rings
- valves

## Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

# ELKALUB



*Hochleistungs-Schmierstoffe*  
*High Performance Lubricants*

## Industry

- plant construction
- miscellaneous

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)