

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



High-temperature oil spray FLC 4010



ELKALUB FLC 4010 is used for the lubrication of chains, joints, rollers, slideways, spindles,

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

gripper seats in the UV- and varnish range for temperatures from -35 °C till +180 °C (+200 °C with constant relubrication). The high creeping ability of ELKALUB FLC 4010 guarantees that the lubricating film is also formed on the inner friction surfaces endangered by wear. After evaporation of the solvent, there remains a transparent, very adhesive film of high compressive strength. ELKALUB FLC 4010 is available as an aerosol and also in liquid form.

[Request product Download data sheet](#)

Base oil

ester oil

Thickener

polyurea

Operating temperature

-35 °C bis 180 °C

Viscosity

160 mm²/s

Suitable for

- slide bearing
- guides, curves

Packaging

- 5 l canister
- 400 ml of aerosol

Industry

- printing industry
- food industry

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

- beverage industry
- pharmaceutical and medical technology
- drive technology
- furniture industry
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com