



MoS₂-grease GLL 10/N1-2

KPF1-2K-20

ELKALUB GLL 10/N1-2 is a long-fibrous, highly adhesive lubricating grease based on lithium soap and containing molybdenumdisulfide (MoS₂). ELKALUB GLL 10/N1-2 is particularly suited for heavy loads in roller and slide bearings as well as for open points of lubrication. The addition of MoS₂ to a basic grease already having a high load carrying capacity, renders

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB GLL 10/N1-2 particularly suited for extremely loaded slide bearings, open cogwheels, joints, cams, rollers and slideways.

[Request product Download data sheet](#)

Base oil

mineral oil

Thickener

lithium (complex)

Operating temperature

-20 °C bis 120 °C

Viscosity

272 mm²/s

NLGI class

1-sehr-weich,2-weich

Suitable for

- slide bearing
- open gears
- racks
- guides, curves

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

Industry

- power tools
- drive technology
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com