



Mounting Paste ELKALUB 22103

ELKALUB 22103 is an assembly paste to prevent tribocorrosion and fretting corrosion. The high percentage of solid lubricants results in pressure-resistant and permanent lubrication of the metal surface; shaft-hub connections, bearings, flanges and other strongly fixed machine parts can be reliably dismantled.

ELKALUB 22103 is suitable for lubrication in the high temperature range up to 700 °C. The polyglycol oil ensures lubrication up to approx. 200 °C; above this temperature the solid inorganic thickener takes over.

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB 22103 can be registered as NSF H1 lubricant and is therefore suitable for use in the food sector or related industries (pharmaceuticals, animal feed, packaging).

[Request product Download data sheet](#)

Base oil

polyglycol

Thickener

inorganic

Operating temperature

-30 °C bis 700 °C

Viscosity

400 mm²/s

NLGI class

1-sehr-weich

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr