



oil spray FLC 3010



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



ELKALUB FLC 3010 is a partly synthetic oil spray which creeps extremely well into fits and joints where it lubricates reliably. The film protecting against corrosion offers a good protection against wear. ELKALUB FLC 3010 is recommended for a temperature range from -20 °C up to +120 °C. ELKALUB FLC 3010 possesses the H1-approval under NSF Registration no. (H1) 126162. Examples for application: Foil transport chains, transmission chains, joints, hinges, bearings, slideways. Note: For areas where there is a larger impact of water, vapour, acids and alkalis (ph-range 2-11 at 50 °C) we recommend our grease spray with H1 approval ELKALUB FLC 367.

[Request product Download data sheet](#)

Base oil

white oil

Operating temperature

-20 °C bis 120 °C

Viscosity

68 mm²/s

Suitable for

- slide bearing
- chains
- pneumatics
- valves
- guides, curves

Packaging

- 400 ml of aerosol

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- drive technology
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com