



KPFK2U-40

ELKALUB GLS 595/N2 is a high temperature grease mainly used for the lubrication of roller and slide bearings in the temperature range from -40 °C up to +250 °C. ELKALUB GLS 595/N2 is resistant to acids and alkalis as well as to organic solvents. Please note: ELKALUB GLS 595/N2 may not be mixed with other lubricants. Due to its high chemical stability ELKALUB GLS 595/N2 has been used for many years as nozzle sealing compound for adhesive machines at the end of the work process. Most important: Before applying the lubricant the surfaces have to be thoroughly cleaned as the lubricant will adhere only to surfaces free of oil, grease and dirt. Recommendation: for cleaning use ELKALUB LFC 500.

[Request product](#) [Download data sheet](#)

Base oil

PFPE

Thickener

solid lubricant

Operating temperature

-40 °C bis 250 °C

Viscosity

360 mm²/s

NLGI class

2-weich

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

Suitable for

- roller bearing
- slide bearing
- assembly grease / fittings / o-rings
- valves

Packaging

- 250 g tube
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- automotive
- food industry
- beverage industry
- pharmaceutical and medical technology
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr