



Poly-alpha-olefin oil LFC 921000



ELKALUB LFC 92100 and ELKALUB LFC 921000 are oils based on hydro carbons. These high-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

quality base oils are responsible for the high viscosity index, provide an excellent aging resistance also at higher temperatures and a very good lubrication. The balanced additives support these properties and makes for a good wear protection and an excellent protection against corrosion.

[Request product Download data sheet](#)

Base oil

other, poly-alpha-olefin

Operating temperature

-40 °C bis 150 °C

Viscosity

1000 mm²/s

Suitable for

- wave gear

Packaging

- 20 l jug
- 200 l barrel

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- power tools
- drive technology
- furniture industry
- wood industry
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com