



Polyglycol fluid grease GLG 886/N00



GPPG00K-30

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB GLG 886 / N00 is a fluid grease for gear lubrication. The polyglycol grease has very good coefficients of friction and is therefore particularly suitable for gearboxes with high sliding components (worm and hypoid gearboxes, screw jacks) ELKALUB GLG 886 / N00 has NSF H1 certification and can therefore be used in food processing areas. A typical area of application is small gear units on filling systems and packaging machines. Please note: ELKALUB GLG 886 / N00 cannot be mixed with conventional mineral oil-based greases. Before use, the compatibility with plastics, elastomers (except EPDM) and coatings (e.g. interior paints) must be checked.

[Request product Download data sheet](#)

Base oil

polyglycol

Thickener

inorganic

Operating temperature

-30 °C bis 120 °C

Viscosity

180 mm²/s

NLGI class

00-fluessig

Suitable for

- gearboxes & gearing
- gearboxes & gearing

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

Packaging

- 2 kg bag
- 18 kg hobbock
- 50 kg hobbock

Industry

- printing industry
- food industry
- beverage industry
- pharmaceutical and medical technology
- drive technology
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com