



polyglycol grease GLS 886/N2



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



KPPG2K-30

[Request product Download data sheet](#)

Base oil

polyglycol

Thickener

inorganic

Operating temperature

-30 °C bis 120 °C

Viscosity

180 mm²/s

NLGI class

2-weich

Suitable for

- roller bearing
- slide bearing
- assembly grease / fittings / o-rings

Packaging

- 250 g tube
- 100 g cartridge
- 380 g LubeShuttle
- 400 g cartridge

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- printing industry
- food industry
- beverage industry
- pharmaceutical and medical technology
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com