



Polyglycol oil LFC 81000

The ELKALUB oils of the 8000 series are polyglycol oils. The oils are used for circulation and gear lubrication. The selected polyglycols are responsible for a low coefficient of friction, a high viscosity index and high oxidation stability. The oils are therefore suitable for lubrication points with larger sliding components (e.g. worm gears, step gears) and applications with special requirements for a constant oil viscosity at changing temperatures and an increased oil life. The EP additive of the LFC 8000 oils ensures a high seizure resistance and very good wear protection for gears and bearings (see also table FZG test). The medium ISO viscosities of the

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB LFC 8000 oils are NSF H1-registration and can therefore be used in the food processing industry or related areas without hesitation. Please note: Polyglycol oils cannot be mixed with mineral oil-based lubricants. Compatibility with plastics, elastomers (except EPDM) and coatings (e.g. interior painting of gears) should be checked before use.

[Request product Download data sheet](#)

Base oil

polyglycol

Operating temperature

-20 °C bis 120 °C

Viscosity

1000 mm²/s

Suitable for

- gearboxes & gearing
- roller bearing
- slide bearing
- worm gear
- gearboxes & gearing

Packaging

- 20 l jug

Industry

- printing industry
- drive technology
- furniture industry
- wood industry
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com