



silicone grease GLS 794/N3



KPSI3R-40

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB GLS 794/N3 is a fully synthetic special grease for application in food, beverage and pharmaceutical industries. It is particularly suited for slide pairings (e.g. taps, valves, fittings) and as a mounting grease. The product is very resistant against water and steam and can be used for operating temperatures from -40 °C up to +180 °C. As a special feature for beverage dispensers and breweries: ELKALUB GLS 794/N3 does not have any influence on the formation of beer foam (see report of TU Munich, 15.06.2016).

[Request product Download data sheet](#)

Base oil

silicone

Thickener

solid lubricant

Operating temperature

-40 °C bis 180 °C

Viscosity

750 mm²/s

NLGI class

3-mittelfest

Suitable for

- assembly grease / fittings / o-rings
- valves

Packaging

- 200 ml brush can
- 250 g tube
- 380 g LubeShuttle

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com