



silicone Spray FLC 745



ELKALUB FLC 745 is a medium-viscous glidant (approx. 260 mm²/s at 40 °C) USDA H1

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

approved (Registration No. 126160) The transparent, non-smelling lubricating film protects and conserves the surface. The product is mainly used in food industries or in printing plants for food packaging. It is suited for foils and plastics (e.g. conveyors) as well as for rubber (e.g. rollers), paper and on metal surfaces. Spray filling with: light hydrocarbons, butane.

Registration no. (H1): 126160

[Request product Download data sheet](#)

Base oil

silicone

Operating temperature

-50 °C bis 170 °C

Viscosity

260 mm²/s

Suitable for

- assembly grease / fittings / o-rings
- guides, curves

Packaging

- 400 ml of aerosol

Industry

- printing industry
- food industry
- drive technology
- furniture industry
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr