Smooth running polyglycol grease VP 885

KPFPG1H-40
Request product Download data sheet

Base oil

polyglycol

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Thickener

solid lubricant, lithium (complex)

Operating temperature

-40 °C bis 100 °C

Viscosity

29 mm^2/s

NLGI class

1-sehr-weich

Suitable for

- gearboxes & gearing
- gearboxes & gearing

Packaging

- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- automotive
- drive technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com