



Special adhesive grease for bearings and gears GLL 6/N2

KP2G-20

ELKALUB GLL 6/N2 is a special grease based on mineral oil. ELKALUB GLL 6/N2 is extremely long-fibred, adhesive and resistant to pressure and centrifugal forces for temperatures from

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

-15 °C up to +100 °C. ELKALUB GLL 6/N2 is used for the lubrication of roller bearings and gears in the low speed range (speed factor ndm [lt] 300.000), for open gear wheels in eccentrics as well as for slow turning slide bearings. ELKALUB GLL 6/N2 has antinoise qualities and is water-resistant.

[Request product](#) [Download data sheet](#)

Base oil

mineral oil

Thickener

lithium (complex)

Operating temperature

-15 °C bis 100 °C

Viscosity

272 mm²/s

NLGI class

2-weich

Suitable for

- roller bearing
- slide bearing
- open gears
- racks

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 18 kg hobbock
- 50 kg hobbock

Industry

- power tools
- drive technology
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com