



Special grease against Tribocorrosion GLS 361/N1

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



KPF1K-25

ELKALUB GLS 361/N1 is a special grease to avoid tribocorrosion. It combines a high load capacity with excellent wear protection against fretting corrosion caused by vibrations/oscillations. **ELKALUB GLS 361/N1** can be used best in open gear drives, shaft to collar connections and all other applications with high frictional wear.

A special use of **ELKALUB GLS 361/N1** is the lubrication of drive cams of the perfecting drum in offset printing machines.

[Fit to go back and forth](#)

[Request product Download data sheet](#)

Base oil

other, white oil

Thickener

polyurea, solid lubricant

Operating temperature

-25 °C bis 1200 °C

Viscosity

100 mm²/s

NLGI class

1-sehr-weich

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

Suitable for

- open gears
- racks

Packaging

- 200 ml brush can
- 100 g cartridge
- 400 g cartridge
- 1 kg can
- 5 kg bucket

Industry

- printing industry
- food industry
- beverage industry
- pharmaceutical and medical technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com