



special-grease GLS 980/N2



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



KPFHC2N-40

ELKALUB GLS 980/N2 is a high-quality multi-purpose grease for application in roller and slide bearings, for slipways as well as for open lubrication points. Due to its synthetic oil base the grease is very resistant to ageing and can be used in a wide temperature range (-40 °C / +140 °C). **ELKALUB GLS 980/N2** is NSF H1-approved and is therefore suited for environments with food contact.

[Request product Download data sheet](#)

Base oil

poly-alpha-olefin, ester oil

Thickener

aluminum complex, solid lubricant

Operating temperature

-40 °C bis 140 °C

Viscosity

220 mm²/s

NLGI class

2-weich

Suitable for

- roller bearing
- slide bearing
- open gears
- guides, curves

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

Packaging

- 250 g tube
- 100 g cartridge
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com