



## Synthetic gear grease VP 903

KPHC2K-30

[Request product Download data sheet](#)

### Base oil

poly-alpha-olefin, ester oil

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)

## Thickener

polyurea

## Operating temperature

-25 °C bis 120 °C

## Viscosity

150 mm<sup>2</sup>/s

## NLGI class

1-sehr-weich, 2-weich

## Suitable for

- gearboxes & gearing
- gearboxes & gearing

## Packaging

- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

## Industry

- power tools

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**