



Universal grease for bearings and gears

GLL 7/N2

KP2K-20

ELKALUB GLL 7/N2 is a lithium-saponified multipurpose grease, which is highly resistant to pressure, adhesive and resistant to oxidation. ELKALUB GLL 7/N2 has a special ELKALUB-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

additivation for the lubrication of roller and slide bearings (under medium up to heavy loads) for temperatures from -20 up to +120° C. ELKALUB GLL 7/N2 is particularly suited for points of lubrication with high centrifugal losses and where there is danger of the lubricant being washed out by water. The grease can be used up to a speed index (ndm*) of about 400.000.

[Request product](#) [Download data sheet](#)

Base oil

mineral oil

Thickener

lithium (complex)

Operating temperature

-20 °C bis 120 °C

Viscosity

97 mm²/s

NLGI class

2-weich

Suitable for

- roller bearing
- slide bearing

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

Industry

- printing industry
- drive technology
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com