ELKALUB
Hochleistungs-Schmierstoffe
High Performance Lubricants

White oil LFC 3150

H1

The oils of the series ELKALUB LFC 3000 are mainly intended for application in the food and

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

drink industry for temperatures from -10 °C (-20 °C) up to +120 °C. These oils are highly resistant to aging and free from resinification. They can be applied in situations where incidental food contact is possible. We possess a USDA H1 approval for all viscosity grades The oils of the series ELKALUB LFC 3000 offer a good protection against corrosion and are well compatible with plastics and sealings. The products are compatible with mineral oils. ELKALUB LFC 3000 oils are mainly applied for gears and chains, as circulation oils, as well as for hydraulic and pneumatic systems.
Request product Download data sheet

Base oil

other, white oil

Operating temperature

-15 °C bis 120 °C

Viscosity

150 mm^2/s

Suitable for

- gearboxes & gearing
- roller bearing
- slide bearing
- chains
- hydraulics
- bed ways
- gearboxes & gearing

Packaging

- 20 l jug
- 200 l barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Industry

- printing industry
- food industry
- beverage industry
- pharmaceutical and medical technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.