

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

H1-Grease for low temperatures LFC 900 AC

ELKALUB LFC 900 AC is an anti-corrosion oil for temporary preservation (e.g., transport preservation) of machines and machine parts. **ELKALUB LFC 900 AC** is NSF H1-registerable; use on machines and machine parts for the food industry or other hygiene-sensitive industrial areas is therefore a preferred application. The corrosion protection of **ELKALUB LFC 900 AC** was assessed in the laboratory and in practical tests (shipping overseas, weathering tests). Due to different machine materials, preservation methods and transport conditions, company-specific tests are recommended before use. **ELKALUB LFC 900 AC** can be applied by dipping, brushing or spraying. Due to the content of less soluble anti-corrosion components, the oil should be stirred before use.

Request product Download data sheet

Base oil

other

Operating temperature

10 °C to 25 °C

Viscosity at 40°C

45 mm^2/s

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Packaging

- 5 l canister
- 750 ml /1 l

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com