

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Chain and adhesive lubricant FLC 8

ELKALUB FLC 8 is a spray, which is based upon our successful special lubricant ELKALUB LA 8. The product does not contain any additives of solid particles. ELKALUB FLC 8 leaves a lubricating film with E.P. and boundary lubrication properties, has a good creeping ability and protects against corrosion. Up to +80 °C, ELKALUB FLC 8 is very adhesive and resistant to centrifugal forces. The lubricating film is very pressure resistant. ELKALUB FLC 8 has shown good results as a special lubricant for highly loaded chains (also in the open air). The product is also used for the lubrication of open gear wheels, cams, cam plates and spindles. Because of the high adhesion of ELKALUB FLC 8, the product is not recommended for long guideways, which need an easy start. ELKALUB FLC 8 has antinoise qualities.

[Request product Download data sheet](#)

Base oil

mineral oil, ester oil

Thickener

polyurea

Operating temperature

-20 °C to 120 °C

Viscosity (active substance)

120 mm²/s

Functionality

- corrosion protection
- lubricant
- creeping

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Suitable for

- slide bearing
- chains
- open gears
- racks
- guides, curves
- fittings & joints

Packaging

- 400 ml of aerosol

Industry

- printing industry
- drive technology
- furniture industry
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com