

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

fluid grease for gears VP 890



GPHC000N-40

ELKALUB VP 890 is a fluid grease for the lubrication of machine elements subject to high loads. Based on synthetic oil, the product guarantees an excellent resistance to ageing which manifests itself in a long-term lubricating effect. This is also valid for an extended temperature range as compared to products based on mineral oils. The grease is suited for oil-tight gearboxes and can easily be pumped in central lubrication systems. ELKALUB VP 890 is NSF H1 approved and can therefore be used in all areas where food, food commodity goods (e.g. packaging material) or pharmaceutical products are processed.

[Request product Download data sheet](#)

Base oil

poly-alpha-olefin

Thickener

polyurea

Operating temperature

-35 °C to 140 °C

Viscosity Base oil

150 mm²/s

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

NLGI class

000-sehr-fluessig

Functionality

- fluid grease
- circulating oil
- low-temperature
- food contact

Suitable for

- gearboxes & gearing
- gearboxes & gearing

Packaging

- 2 kg bag
- 18 kg hobbock
- 50 kg hobbock

Industry

- printing industry
- food industry
- beverage industry
- pharmaceutical and medical technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com