



High-temperature grease GLS 966/N2

KPHC2P-40

[Request product](#) [Download data sheet](#)

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Base oil

poly-alpha-olefin

Thickener

polyurea, solid lubricant

Operating temperature

-40 °C to 160 °C

Viscosity Base oil

150 mm²/s

NLGI class

2-weich

Functionality

- low-temperature
- high temperature

Suitable for

- roller bearing
- slide bearing
- racks

Packaging

- 250 g tube
- 400 g cartridge
- 1 kg can
- 5 kg bucket

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- 18 kg hobbock
- 50 kg hobbock

Industry

- power tools
- wood industry
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com