

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Hybrid grease VPG 934

High-temperature hybrid grease for loaded bearings. **ELKALUB VPG 934** is used successfully in pump bearings.

[Request product](#) [Download data sheet](#)

Base oil

poly-alpha-olefin, PFPE

Thickener

polyurea

Operating temperature

-40 °C to 180 °C

Viscosity Base oil

80 mm²/s

Suitable for

- roller bearing

Packaging

- 400 g cartridge

Industry

- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com