

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

PFPE high-temperature grease GLS 595/N3



KPFK3U-40

ELKALUB GLS 595/N3 is a high temperature grease for the lubrication of slowturning plain and antifriction bearings for temperatures from -40 °C up to +250 °C.

ELKALUB GLS 595/N3 is resistant to acids and alkalis as well as to organic solvents.

ELKALUB GLS 595/N3 may not be mixed with other lubricants. Most important: Before applying the lubricant the surfaces have to be thoroughly cleaned as the lubricant will adhere only to surfaces free of oil, grease and dirt. Recommendation: for cleaning use ELKALUB LFC 500.

[Request product Download data sheet](#)

Base oil

PFPE

Thickener

solid lubricant

Operating temperature

-40 °C to 250 °C

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Viscosity Base oil

360 mm²/s

NLGI class

3-mittelfest

Functionality

- food contact
- mounting devices

Suitable for

- roller bearing
- valves
- assembly grease / fittings / o-rings

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- automotive
- food industry
- beverage industry
- pharmaceutical and medical technology
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com