

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

silicone grease GLS 794/N1



KPSi1R-40

ELKALUB GLS 794/N1 is a fully synthetic special grease for use in the food and beverage industry (sliding processes, e.g. taps, valves, fittings). The formation of the beer foam is not influenced by ELKALUB GLS 794/N1 (see report Weihenstephan). The product has good resistance to water and water vapor and can be used in the temperature range from -40 °C to + 180 °C. ELKALUB GLS 794 / N1 owns the USDA H1 Approval (occasionally allowed contact with food).

[Request product Download data sheet](#)

Base oil

silicone

Thickener

solid lubricant

Operating temperature

-40 °C to 180 °C

Viscosity Base oil

750 mm²/s

NLGI class

1-sehr-weich

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Functionality

- low-temperature
- food contact
- mounting devices

Suitable for

- assembly grease / fittings / o-rings
- valves

Industry

- food industry
- beverage industry
- pharmaceutical and medical technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com