

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Special Grease GLL 1

KP2K-20

ELKALUB GLL 1 is a mineral oil based grease especially for the lubrication of roller and slide bearings in the temperature range from -20 °C up to + 120 °C. The product offers an excellent protection against wear and corrosion.

Due to its paste-like consistency the grease dissolves well and without residues in lubricating oils and is therefore suited for a multitude of assembly applications (e.g. pre-lubrication of slide bearings, seal installation - no EPDM).

[Request product Download data sheet](#)

Base oil

mineral oil, ester oil

Thickener

lithium (complex)

Operating temperature

-20 °C to 120 °C

Viscosity Base oil

68 mm²/s

Packaging

- 1 kg can
- 5 kg bucket
- 50 kg hobbock
- 250 g tube

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com