



Special grease GLS 135/N2

KP2K-20

ELKALUB GLS 135/N2 is a lithium-saponified, water resistant and corrosion inhibiting universal grease. It can be used for roller and slide bearings in the temperature range from -20 °C to +120 °C. The short-fibred and homogeneous grease is excellently suitable for the lubrication of linear guidance systems as well as for ball bearings up to a speed factor ndm of

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

500.000. ELKALUB GLS 135/N2 has a very low oil bleeding and separation tendency. Therefore it is well conveyable in central lubricating systems (conveying test at bielomatik and Lincoln).

[Request product Download data sheet](#)

Base oil

mineral oil, ester oil

Thickener

lithium (complex)

Operating temperature

-20 °C to 120 °C

Viscosity Base oil

100 mm²/s

NLGI class

2-weich

Suitable for

- roller bearing
- slide bearing
- linear guides, ball screws
- guides, curves

Packaging

- 250 g tube
- 100 g cartridge
- 380 g LubeShuttle
- 400 g cartridge

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- printing industry
- drive technology
- wood industry
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com