

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Spezial grease GLS 135/N1

KP1K-20

ELKALUB GLS 135/N1 is a lithium-saponified, water resistant universal grease of high efficiency. ELKALUB GLS 135/N1 protects against corrosion and can be used for roller and slide bearings in the temperature range from -20 °C up to +120 °C. The short-fibred and homogeneous grease is excellently suitable for the lubrication of ball bearings up to a speed factor ndm of 500.000. as well as for linear units. ELKALUB GLS 135/N1 is well conveyable in central lubricating systems.

[Request product Download data sheet](#)

Base oil

mineral oil, ester oil

Thickener

lithium (complex)

Operating temperature

-20 °C to 120 °C

Viscosity Base oil

100 mm²/s

NLGI class

1-sehr-weich

Suitable for

- roller bearing
- slide bearing
- linear guides, ball screws
- guides, curves

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Packaging

- 250 g tube
- 100 g cartridge
- 380 g LubeShuttle
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 50 kg hobbock
- 18 kg hobbock

Industry

- printing industry
- drive technology
- wood industry
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com