

Chain and adhesive lubricant FLC 8

ELKALUB FLC 8 is a spray, which is based upon our successful special lubricant ELKALUB LA 8. The product does not contain any additives of solid particles. ELKALUB FLC 8 leaves a lubricating film with E.P. and boundary lubrication properties, has a good creeping ability and protects against corrosion. Up to +80 °C, ELKALUB FLC 8 is very adhesive and resistant to centrifugal forces. The lubricating film is very pressure resistant. ELKALUB FLC 8 has shown good results as a special lubricant for highly loaded chains (also in the open air). The product is also used for the lubrication of open gear wheels, cams, cam plates and spindles. Because of the high adhesion of ELKALUB FLC 8, the product is not recommended for long guiderails, which need an easy start. ELKALUB FLC 8 has antinoise qualities.
Request product Download data sheet

Base oil

mineral oil, ester oil

Thickener

polyurea

Operating temperature

-20 °C to 120 °C

Viscosity (active substance)

120 mm²/s

Functionality

- corrosion protection
- lubricant
- creeping

Suitable for

- slide bearing
- chains
- open gears

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- racks
- guides, curves
- fittings & joints

Packaging

- 400 ml of aerosol

Industry

- printing industry
- drive technology
- furniture industry
- plant construction

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com