

Grease for plastic-steel pairings VP 905

KFHC0M-30
Request product Download data sheet

Base oil

poly-alpha-olefin, ester oil

Thickener

solid lubricant, lithium (complex)

Operating temperature

-30 °C to 120 °C

Viscosity Base oil

360 mm²/s

NLGI class

- 0 | semi-liquids
- 1 | very soft

Functionality

- lubricant
- low-temperature

Suitable for

- gearboxes & gearing
- roller bearing
- slide bearing
- linear guides, ball screws

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- valves
- gearboxes & gearing

Packaging

- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- automotive
- power tools
- drive technology
- furniture industry
- bearing manufacturer

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com