

High-load grease GLS 131/N2

KP2K-20
ELKALUB GLS 131/N2 is a universal grease with high pressure absorption and very good adhesion. The grease can be used in roller and plain bearings as well as in open lubrication points. The speed characteristic in ball bearings is 250,000 mm / min-1.
Request product Download data sheet

Base oil

mineral oil

Thickener

lithium (complex)

Operating temperature

-20 °C to 130 °C

Viscosity Base oil

320 mm²/s

NLGI class

- 2 | soft

Functionality

- lubricant
- universal lubricant
- high pressure resistant

Suitable for

- roller bearing
- slide bearing

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- guides, curves

Packaging

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

Industry

- drive technology
- bearing manufacturer
- plant construction
- miscellaneous

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com