

High-performance mineral oil with adhesive additives LFC 1320H

ELKALUB oils of the 1000 H series are CLP oils with particularly high adhesion. They are particularly suitable for lubrication points with high spin losses, e.g. Chains or open gears as well as gears and bearings in the temperature range up to 120 °C. The adhesive oils offer high wear and corrosion protection as well as excellent pressure absorption capacity. Special aging stabilizers and fine filtration ensure long service life and high operational reliability. They should be used according to the viscosity specifications of the machine manufacturer. All oils of the ELKALUB LFC 1000 H series are free of PCB and chlorine-containing compounds and can be disposed of as waste oil.
Request product Download data sheet

Base oil

mineral oil, ester oil

Operating temperature

-10 °C to 120 °C

Viscosity at 40°C

320 mm²/s

Functionality

- lubricant

Suitable for

- roller bearing
- slide bearing
- chains
- bed ways

Packaging

- 20 l jug
- 200 l barrel

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

Industry

- printing industry
- drive technology
- furniture industry
- wood industry
- bearing manufacturer
- plant construction

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com