

**High-load grease GLS 131/N2**

KP2K-20
ELKALUB GLS 131/N2 is a universal grease with high pressure absorption and very good adhesion. The grease can be used in roller and plain bearings as well as in open lubrication points. The speed characteristic in ball bearings is 250,000 mm / min-1.
Request product Download data sheet

**Base oil**

mineral oil

**Thickener**

lithium (complex)

**Operating temperature**

-20 °C to 130 °C

**Viscosity Base oil**

320 mm²/s

**NLGI class**

- 2 | soft

**Functionality**

- lubricant
- universal lubricant
- high pressure resistant

**Suitable for**

- roller bearing
- slide bearing

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- guides, curves

**Packaging**

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock

**Industry**

- drive technology
- bearing manufacturer
- plant construction
- miscellaneous

Diese Daten entsprechen unserem derzeitigen Kenntnisstand und wurden nach besten Wissen erstellt. Änderungen und/ oder Ergänzungen behalten wir uns vor.



ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com